



IPP 1032

2 Megapixel

IP Dome Camera

Designed for professional indoor applications, where the FULL HD resolution and the 24 hs reliable recording are needed.

Featured specifications

- H.265+/ H.265 / H.264+ / H.264
- 2 Megapixel
- Siera CLOUD
- Dual Streaming
- 3.6 Fixed Lens
- PoE
- SIERA DDNS
- ONVIF
- Indoor
- ABS Case
- 25 mts IR Range
- Encrypted Communication
- Auto Frame Rate adapter according to the network bandwidth
- Mobile phone and Webserver viewer
- Siera CMS for 128 cameras (Win / MAC)

Sensor:	1/3" / 2Mpx
Lens:	3.6 mm
Electronic Shutter:	1/25s~1/100,000s
Illumination min.:	0,08 Lux
Image resolution supported:	2MPX 1920*1080
Frame Rate:	1~30fps
Video Compression:	H.265+/ H.265 / H.264+ / H.264
Video Bite Rate:	32K~16Mbps adjustable
Digital Noise Reduction:	3D DNR
Privacy masking:	4 zones
Day/Night Function:	IR CUT
IR Range:	25mts
Bracket:	Wall and Ceiling
Video Settings:	Saturation, Brightness, Shutter, Contrast, AGC, Iris, Backlight, Flicker, Mirror, IR
Data Stream:	Video and data
Ethernet:	1-ch 10/100M, RJ45
Main Processor:	High performance microprocessor
Operation System:	Embedded Linux
Security:	Password protection, multi-level user
View:	Webserver, CMS and Mobile through Siera iSMS 5.0
Compatibility:	ONVIF
Smartphone app :	iSMS 5.0 (available in iOS and Android)
Network Protocol:	TCP/IP/HTTP/RTSP/FTP/PPPoE/RTCP/SMTP/DHCP/DDNS/ NTP/UPnP/SNMP
Working Temperature:	-20° - 50°C
Working Humidity:	<95%
Power:	DC12V / PoE
Consumption:	10W / 0,5A
Dimension:	100(W) x 70(H)mm
Weight:	0,2 Kg

