



PRO 9052IP-2MPX-IVS

2MPX Target Capture Bullet IP Camera

Siera manufactures reliable and affordable solutions in Electronic Security, CCTV, Access Control, Intercommunication and Professional Audio.

Featured specifications

- 1/2.8" Sensor
- 2.7 - 13.5mm motorized lens
- 25fps/30fps@2MP(1920*1080)
- Triple streams
- Support human body, vehicle, non-motor detection and capture
- WDR, 3D DNR, ROI, Defog, HLC, Anti-shake
- Smart IR up to 30m
- IP67
- FREE IPX PRO V4 VMS
- FREE iOS and Android APP
- Onvif

CAMERA	
Image Sensor	1/2.8" Progressive Scan CMOS
Effective Pixels	1920(H)×1080(V)
Electronic Shutter	1/5-1/20,000s
Min. illumination	Color: 0.01Lux @(F1.2,AGC ON), B/W: 0Lux @(IR LED ON)
S/N Ratio	55dB
Day/Night	ICR
Wide Dynamic Range	WDR (120dB)
IR Range	Up to 30m
IR On/Off Control	Auto/ Manual
IR LEDs	30pcs
Pan/Tilt/Rotation Range	Pan: 0°~360°, Tilt: 0°~90°, Rotation: 0°~360°
LENS	
Lens Type	Motorized
Iris	Fixed Iris
Focal Length	2.7~13.5mm
F Number	F1.6
Angle of View	H: 105°~ 30°, V: 55°~15°
Focus Control	Motorized
VIDEO	
Compression	H.265, H.264, MJPEG
Max. Resolution	1080P(1920×1080)
Streaming Capability	3 Streams
Stream / Frame Rate	Stream1: 1920×1080/1280×720 @25/30fps Stream2: D1/VGA/640×360/CIF/QVGA @25/30fps Stream3: VGA/CIF/QVGA @25/30fps
Bit Rate Control	CBR/VBR
Bit Rate	Stream1: 200kbps~12000kbps Stream2: 100kbps~6000kbps Stream3: 100kbps~3000kbps
Image Enhancement	HLC / BLC / Anti-shake / Defog / WDR (120dB)
White Balance	Support
Gain Control	Auto/Manual
Noise Reduction	2D/3D DNR
Smart IR	Support
Mirror	Support
Region of Interest	Support
Motion Detection	Support
Privacy Masking	Support



PRO 9052IP-2MPX-IVS

2MPX Target Capture Bullet IP Camera



AUDIO	
Compression	G.711, RAW_PCM
Bit Rate	8kbps, 16kbps, 64kbps
NETWORK	
Protocols	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTP/RTCP, PPPoE, SMTP, DNS, UPnP, FTP, ARP, SNMP
Interoperability	ONVIF, SDK, CGI
Streaming Method	Unicast
Max. User Access	10 Users
Web Viewer	<IE11, Chrome, Firefox
Management Software	IPX PRO V4
Smart Phone	IOS, Android
INTELLIGENCE	
IVS	Perimeter, Single Virtual Fence, Double Virtual Fences, Multi Loiter, Converse, People counting Support alarm triggering by specified target types (human and vehicle). Filtering out mistaken alarm caused by target types such as leaf, light, animal, and flag, etc.
Smart Detection	Detects human body, vehicle and non-motor automatically detection and capture
INTERFACE	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio	1ch Input, 1ch Output
Alarm	1ch Input, 1ch Output
Reset Button	Support
Storage	Built-in Micro SD slot, up to 128G
ELECTRICAL	
Power Supply	DC12V/POE (IEEE 802.3af)
Power Consumption	<8.5W
Operating Temperature	-30°C ~ 50°C (-22°F ~ 122°F)
Operating Humidity	Less than 90% RH
Ingress Protection	IP67
Certifications	CE / FCC
Casing	Metal
Dimensions	232x74.8x80mm
Net Weight	700g