



PRO 9172IP-2MPX-IVS
 2MPX XTREME PROFESSIONAL
 IP Pinhole Camera with IVS

Siera manufactures reliable and affordable solutions in Electronic Security, CCTV, Access Control, Intercommunication and Professional Audio.

Featured specifications

- 1/2.8" Sensor
- 3.7mm
- 2MPX Resolution
- Multiple Streams
- WDR, 3D, DNR
- ROI, HLC, Defog, Corridor Mode
- FREE Siera DDNS
- FREE IPX-PRO V4 VMS
- FREE APP for iOS / Android
- ONVIF

Image Sensor:	1/2.8" Sensor
Min. Illumination:	Color 0.05Lux(AGC ON); B&W 0.005Lux(AGC ON)
Day & Night:	Fixed
Shutter Speed:	1/2-1/100000s
Auto Iris:	Fixed
Wide Dynamic Range:	WDR>120dB
Digital Noise Reduction:	3D
Lens:	3.7mm
FOV:	84°
Video Compression:	H.265/H.264/MJPEG
Bit Rate (CBR / VBR):	Main stream: 500Kb-12000Kb; Sub stream: 200Kb-8000Kb
Audio Compression:	G711_A, G711_U, RAW_PCM, NONE
Max. Resolution:	1920x1080/30fps
Stream:	Stream1 1920x1080 / 1280x720 Stream 2 D1 / VGA / 640x360 / CIF / QVGA
Image Setting:	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
HLC:	Auto
9:16 Corridor Mode:	Yes
ROI:	Yes
Defog:	Yes
Network Protocols:	IPv4, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ICMP, IGMP, Unicast and Multicast
Alarm Trigger:	Perimeter, Single Virtual Fences, Double Virtual Fences, Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed, Converse, Illegal Parking, Signal Bad, MotionDetection, Network disconnect, Disk alarm, I/O alarm
RTSP Video:	Standard RFC2326, Support QuickTime / VLC Player
Security:	User security authentication, Reset, Hardware Watch Dog
Web Language:	English, Portuguese, Spanish
System Compatibility:	Onvif
Ethernet:	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio I/O:	1ch Audio In,1ch Audio Out
Alarm I/O:	2ch Alarm In,1ch Alarm Out
RS485:	Yes
BNC Output	Yes
Edge Storage:	SD/SDHC Max.256Gb
Power Supply:	DC12V
Power Consumption:	3W(MAX)



PRO 9172IP-2MPX-IVS
2MPX XTREME PROFESSIONAL IP Pinhole Camera with IVS



Operating Temperature:	Starting Temperature: -10°C ~ 50°C (14°F ~ 122°F) Working Temperature: -20°C ~ 50°C (-4°F ~ 122°F)
Operating Humidity:	0% - 90% RH
Approvals:	CE / FCC
Product Dimensions:	37.6 x 32.8 x 46.5mm
Product Weight:	180g