



PRO 9832IP-32MPX
32MPX
Multi-Sensor IP Camera

Designed for outdoor professional applications where the large cover view with only one camera, high resolution, 360° Panoramic View and Bandwidth Control are needed.

Featured specifications

- 4pcs 1/1.8" 8MP sensor
- H.265/H.264 triple-stream encoding
- 25fps@7680×4320
- 720° panoramic view
- De-warping image
- Support camera & software de-warping
- ROI, Defog, HLC, BLC, AWB, AGC, EIS, IVS
- IP66
- FREE Siera DDNS
- FREE IPX-PRO V4 VMS

| | |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor | 4pcs 1/1.8" 8MP Sensor |
| Effective Pixels | 7680(H)×4320(V) |
| Electronic Shutter | 1/5-1/20,000s |
| Min. illumination | Color:0.002Lux@(F2.2, AGC ON) B/W:0.0002Lux@(F2.2, AGC ON) |
| S/N Ratio | ≥55dB |
| Day/Night | ICR |
| Wide Dynamic Range | DWDR |
| Lens Type | Fixed |
| Iris | Fixed Iris |
| Focal Length | 2.2mm |
| F Number | F2.2 |
| Angle of View | 360°×360° |
| Focus Control | Fixed |
| Compression | H.265, H.264, MJPEG |
| Max. Resolution | Edge stitching 7680×4320 |
| Streaming Capability | 3 Streams |
| Stream / Frame Rate | Stream1: 7680×4320 @25fps,5760×3240/3840×2160 @25fps/30fps Stream2: 2560×1440/1080P/D1 @25fps/30fps Stream3: 720P/640×360/D1 @25fps/30fps |
| Bit Rate Control | CBR/VBR |
| Bit Rate | Stream1: 500Kbps~16Mbps Stream2: 500Kbps~12Mbps Stream3: 100Kbps~8Mbps |
| Image Enhancement | HLC / BLC / Anti-shake / Defog / DWDR |
| White Balance | Support |
| Gain Control | Auto/Manual |
| Noise Reduction | 2D/3D DNR |
| Region of Interest | Support |
| Motion Detection | Support |
| Privacy Masking | Support |
| Video Mode | Full Screen Stretch, 360 degrees panorama, Crystal Ball, Asteroid, Auto Cruise |
| Compression | G.711 |
| Bit Rate | 64kbps (G.711), 128kps (RAW_PCM) |
| Protocols: | IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTPC/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ARP, SNMP |
| Interoperability | ONVIF, SDK, CGI |
| Streaming Method | Unicast |
| Max. User Access | 10 Users |
| Web Viewer | <IE11, Chrome, Firefox |
| Smart Phone | iOS, Android |



PRO 9832IP-32MPX

32MPX Multi-Sensor IP Camera



| | |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IVS | Perimeter, Single Virtual Fence, Double Virtual Fences, Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed, Converse, Illegal Parking, Signal Bad |
| Ethernet | 1 Ethernet (10/100 Base-T) RJ-45 Connector |
| Audio | 1ch Input, 1ch Output, 2ch Built-in MIC |
| Alarm | 1ch Input, 1ch Output |
| Reset Button | Support |
| Power Supply | DC12V/POE+ (IEEE 802.3at) |
| Power Consumption | ≤10W |
| Operating Temperature | Starting Temperature: -30°C ~ 60°C (-22°F ~ 140°F) Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) |
| Operating Humidity | Less than 90% RH |
| Ingress Protection | IP66 |
| Certifications | CE / FCC |
| Casing | Metal |
| Dimensions | 112.2×112.2×90mm |
| Net Weight | 1.25Kg |