



SAC 4103
UHF Sticker

Siera manufactures reliable and affordable solutions in electronic security, CCTV, Access Control, Intercom and Professional Audio.

Featured specifications

- UHF RFID Sticker
- Frequency 860-928Mhz
- 15m range
- EPC 128bits TID 48bits
- Internal Installation
- Tamper Proof
- High data retention
- Reading speed 10m/s

| | |
|------------------------------|--|
| Power: | Passive TAGs (No power) |
| Frequency: | UHF 860 MHz a 928 MHz EPC Class 1 Gen 2, ISO 18000-6C Standard |
| Reading Speed: | 10ms/64bits single card reading |
| Supported Protocol: | ISO 18000-6B, ISO 18000-6C (EPC GEN2) |
| IC Chip: | Alien Higgs-9 |
| TAG Printing: | W26 and W34 Bit Decimal Data Printing |
| Adhesion Type: | Tamper Proof, Damage to IC Chip and/or antenna when trying to remove |
| Installation Type: | Internal (Windshield) |
| Working Mode: | FHSS |
| Programming Capacity: | 96bits |
| Maximum EPC Memory: | 96bits |
| Maximum User Memory: | 688bit |
| EPC/TID: | 128/48bits |
| Data Retention: | Minimum 10 years with UV protection and ambient temperature 45°C |
| Operating Humidity: | 95% |
| Working Temperature: | -20°C to 80°C |
| Weight: | 1gr. |
| Color: | Grey |
| Dimensions: | 93 x 14 mm |
| Storage Temperature: | -40°C to 100°C |

