



SDR 1432S-V2

32 Ch.

Ultra HD Network Video Recorder

Smart NVR / Designed for professional security applications. Ease settings interface. Special and ease interface for search, playback and backup. 5MPX resolution supported in all the channels. Remote viewing in: Win, Mac, iPhone, iPad, iPod, Android phones, Android tablets, Android device TV, etc. Free Siera DDNS. WiFi and 4G modules optional. Double video outputs at the same time: VGA, HDMI. Silent system. Free 192 cameras VMS.

Featured specifications:

- H.265+/H.265/H.264+/H.264
- 4K cameras supported
- ONVIF
- 2 HDD (20TB total)
- Siera CLOUD
- SIERA DDNS
- HDMI
- 4G and WiFi modules (optional)
- Mobile phone and Webserver viewer
- Siera VMS for 192 cameras (Win / MAC)

Main Processor:	High Performance Embedded Microprocessor
Operation System:	Embedded Linux OS
System Resource:	Pentaplex
Operation Interface:	Mouse, Rear Panel
Video Split:	1/4/8/9/16/32
Video Resolution:	32 ch 5MPX QXSGA (2560x1920) 16 ch 8MPX 4K (4096x2160)
Video Compression:	H.265+/H.265/H.264+/H.264
Image Control:	Configurable
Motion Detection:	Configurable detection areas and Sensitivity
Recording Priority:	Manual > Motion Detection > Schedule
Playback Search:	Date, Time, Event, Channel
Smartphone app:	iSMS 7.0 (available in iOS and Android)
Video Storage:	HDD / Network
USB HDD U-Disk:	Supported
USB DVD Burner:	Supported
Backup Mode:	Network / USB / HDD
Video Output:	VGA, HDMI
Ethernet Interface:	RJ45 10M/100/1000M Base-TX
USB Interface:	2 x USB2.0
4G and Wifi modules:	Supported (not included)
HDD/SATA Interface:	2 x SATA up to 10Tb each one
TCP/IP Ports:	80 / 3333 / 5800
UDP Ports:	37778 / 554
Network Protocols:	TCP/IP/DHCP/DDNS/NTP/SMTP/PPPoE/FTP/DNS/UPNP
PTZ:	Pan, Tilt, Zoom, Preset, Cruise, Trace
Power Supply: Power Consumption:	DC12V±10% - 100 / 240VAC - Power Adaptor Included < 30W (HDD not included)
Working Temperature:	-10°C ~ +60°C
Working Humidity:	10%~90%
Dimensions:	326 x 243 x 51mm
Weight:	1.1 kg (HDD not included)

