



IPL 2432IP/28-4MPX-IVS-NGS-S-FR

4 Megapixel

NightGuardian IP Dome Camera with Analytics

Designed for professional indoor applications, where the ULTRA HD Resolution, color image during night and the 24 hs reliable recording are needed.

Featured specifications

- H.265+
- 4 Megapixel
- Warm light full color at night
- IVS: Face detection, Human detection, Line crossing, Intrusion detection.
- Siera CLOUD
- Dual Streaming
- 2.8mm Fixed Lens
- PoE
- SD Card Slot (256 GB Máx)
- SIERA DDNS
- ONVIF
- Indoor
- Metal Case
- 20 mts NightGuardian vision in color
- Encrypted Communication
- Auto Frame Rate adapter according to the network bandwidth
- Mobile phone and Webserver viewer
- Siera VMS for 192 cameras (Win / MAC)

Sensor:	1/3" / 4Mpx
Lens:	2.8mm fixed Lens
Electronic Shutter:	1/25s~1/100,000s
Illumination min.:	3 Lux Led On Warm Light
Image resolution supported:	2592*1520
Analytics:	Face detection, Human detection, Line crossing, Intrusion
Frame Rate:	1-25/30fps
Video Compression:	H.265+
Video Bite Rate:	32K~16Mbps adjustable
Privacy masking:	4 zones
Day/Night Function:	NightGuardian color or B/W
NightGuardian Range:	20mts
Video Settings:	Saturation, Brightness, Shutter, Contrast, AGC, Iris, Backlight, Flicker, Mirror, IR
Data Stream:	Video and data
Ethernet:	1-ch 10/100M, RJ45
Main Processor:	High performance microprocessor
Operation System:	Embedded Linux
Security:	Password protection, multi-level user
View:	Webserver, VMS and Mobile through Siera iSMS 7.0
Compatibility:	ONVIF
Smartphone app:	iSMS 7.0 (available in iOS and Android)
Network Protocol:	TCP/IP/HTTP/RTSP/FTP/PPPoE/RTCP/SMTP/DHCP/DDNS/NTP/UPnP/SNMP
SD Card Slot:	Supported, up to 256GB
Working Temperature:	-20° to 55°C
Working Humidity:	<95%
Power:	DC12V / PoE
Consumption:	10W / 0,5A
Dimension:	150 x 120 mm
Weight:	0,8 kg

