



## PRO 9032IP-8MPX-IVS-A

8MPX

IP Camera with Strobe Light

*Siera manufactures reliable and affordable solutions in Electronic Security, CCTV, Access Control, Intercommunication and Professional Audio.*

### Featured specifications

- 8MPX
- WDR
- Face, human and vehicle detection
- IVS: people counting, intrusion, single line crossing, double line crossing, loitering and wrong way
- Audio and Alarm I/O
- Built-in microphone
- Strobe-light alarms linkage to warn intruders
- 30mts IR distance
- SD card slot
- IP66
- PoE
- FREE Siera DDNS
- IPX-PRO V4 compatible

<b>Image Sensor</b>	1/2.8"
<b>Resolution</b>	8MPX (3840x2160)
<b>Electronic Shutter</b>	Auto/Manual, 1/5 ~ 1/20,000s
<b>Min. illumination</b>	Color: 0.01 Lux @ (F1.6, AGC ON) , B/W: 0 Lux @ (IR LED ON)
<b>Day &amp; Night</b>	IR cut filter
<b>IR Distance</b>	30mts
<b>Illumination On/Off Control</b>	Auto/Manual
<b>Pan/Tilt/Rotation Range</b>	Pan: 0° ~ 355°, Tilt: 0° ~ 80°, Rotation: 0° ~ 360°
<b>Focal Length</b>	2.8 mm Fixed Iris
<b>Angle of View</b>	H: 97.4°, V: 52.5°
<b>Streaming Capability</b>	3 Streams
<b>Stream/Frame Rate</b>	Stream1: 3840x2160, 2592x1944, 2592x1520, 2560x1440, 2304x1296, 1920x1080, 1280x720 @ 25/30fps Stream2: D1, VGA, CIF @ 25/30fps Stream3: VGA, CIF, QVGA @ 25/30fps
<b>Bit Rate Control</b>	CBR/VBR
<b>Bit Rate</b>	Stream1: 200kbps~16Mbps Stream2: 100kbps~6Mbps Stream3: 100kbps~3Mbps
<b>Region of Interest</b>	Off/On (8 Zone, Rectangle)
<b>Image Adjustment</b>	Brightness, Sharpness, Contrast, Saturation adjustable
<b>Aisle Mode</b>	Supported
<b>Mirror</b>	Supported
<b>White Balance</b>	Auto/Manual
<b>Day/Night Setting</b>	Auto, Day, Night, Time
<b>Smart IR</b>	Supported
<b>Noise Reduction</b>	2D/3D DNR
<b>Image Enhancement</b>	HLC, BLC, Defog
<b>Wide Dynamic Range</b>	WDR 55dB
<b>Motion Detection</b>	Supported
<b>Privacy Masking</b>	Supported
<b>IVS</b>	Face, human and vehicle detection, Intrusion, Single line crossing, Double line crossing, Loitering, Wrong way, P People counting Support alarm triggering by specified target types (human and vehicle)
<b>Smart Alarm</b>	When an alarm is triggered, active strobe light to warn intruders
<b>Compression</b>	G.711, RAW_PCM
<b>Bit Rate</b>	8kbps, 16kps, 64kbps
<b>Protocols</b>	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTPC/RTP, PPPoE, SMTP, DNS, UPnP, FTP, SNMP, SSL



## PRO 9032IP-8MPX-IVS-A

8MPX IP Camera with Strobe Light



<b>Interoperability</b>	ONVIF, SDK and CGI
<b>Streaming Method</b>	Unicast
<b>Max. User Access</b>	10 Users
<b>Web</b>	<IE11, Chrome, Firefox and Edge
<b>Language</b>	Multi Language
<b>Network Interface</b>	1 Ethernet (10/100 Base-T) RJ-45 Connector
<b>Audio Interface</b>	1ch Input, 1ch Output
<b>Built-in Microphone</b>	Yes
<b>Alarm Interface</b>	1ch Input, 1ch Output
<b>Reset Button</b>	Supported
<b>SD Card slot</b>	Built-in, up to 256GB ( not included )
<b>Power Supply</b>	DC12V (-15%~+25%)/PoE (IEEE 802.3af )
<b>Power Consumption</b>	8 W
<b>Operating Temperature</b>	-40°C ~ 60°C
<b>Operating Humidity</b>	90%
<b>Ingress Protection</b>	IP66
<b>Casing</b>	Metal and Plastic
<b>Dimensions</b>	118x94mm
<b>Net Weight</b>	0.55 kg