



PRO 9062IP-2MPX-IVS
 2MPX Facial Recognition
 and Population Control Bullet IP Camera

Siera manufactures reliable and affordable solutions in Electronic Security, CCTV, Access Control, Intercommunication and Professional Audio.

Featured specifications

- 1/2.8" Sensor
- 2.7 - 13.5mm motorized lens
- 25fps/30fps@2MP(1920*1080)
- Triple streams
- Facial Recognition
- Population Control
- People Counting
- Support face, human body, vehicle, non-motor detection and capture
- WDR, 3D DNR, ROI, Defog, HLC, Anti-shake
- Smart IR up to 40m
- IP66
- FREE IPX PRO V4 VMS
- FREE iOS and Android APP
- Onvif

| | |
|----------------------|---|
| CAMERA | |
| Image Sensor | 1/2.8" Progressive Scan CMOS |
| Effective Pixels | 1920(H)×1080(V) |
| Electronic Shutter | 1/5-1/20,000s |
| Min. illumination | Color: 0.01Lux @(F1.2,AGC ON), B/W: 0Lux @(IR LED ON) |
| S/N Ratio | 55dB |
| Day/Night | ICR |
| Wide Dynamic Range | WDR (120dB) |
| IR Range | Up to 40m |
| IR On/Off Control | Auto/ Manual |
| IR LEDs | 30pcs |
| LENS | |
| Lens Type | Motorized |
| Iris | Fixed Iris |
| Focal Length | 2.7~13.5mm |
| F Number | F1.6 |
| Angle of View | H: 105°~ 30°, V: 55°~15° |
| Focus Control | Motorized |
| VIDEO | |
| Compression | H.265, H.264, MJPEG |
| Max. Resolution | 1080P(1920×1080) |
| Streaming Capability | 3 Streams |
| Stream / Frame Rate | Stream1: 1920×1080/1280×720 @25/30fps Stream2: D1/VGA/640×360/CIF/QVGA @25/30fps Stream3: VGA/ CIF/QVGA @25/30fps |
| Bit Rate Control | CBR/VBR |
| Bit Rate | Stream1: 200kbps~1200kbps Stream2: 100kbps~6000kbps Stream3: 100kbps~3000kbps |
| Image Enhancement | HLC / BLC / Anti-shake / Defog / WDR |
| White Balance | (120dB) Support |
| Gain Control | Auto/Manual |
| Noise Reduction | 2D/3D DNR |
| Smart IR | Support |
| Mirror | Support |
| Region of Interest | Support |
| Motion Detection | Support |
| Privacy Masking | Support |



PRO 9062IP-2MPX-IVS

2MPX Facial Recognition and Population Control Bullet IP Camera



| | |
|-----------------------|---|
| AUDIO | |
| Compression | G.711, RAW_PCM |
| Bit Rate | 8kbps, 16kbps, 64kbps |
| NETWORK | |
| Protocols | IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ARP, SNMP |
| Interoperability | ONVIF, SDK, CGI |
| Streaming Method | Unicast |
| Max. User Access | 10 Users |
| Web Viewer | <IE11, Chrome, Firefox |
| Management Software | IPX PRO V4 |
| Smart Phone | IOS, Android |
| INTELLIGENCE | |
| IVS | Perimeter, Single Virtual Fence, Double Virtual Fences, Multi Loiter, Converse, People counting Support alarm triggering by specified target types (human and vehicle).Filtering out mistaken alarm caused by target types such as leaf, light, animal, and flag, etc. |
| Smart Detection | Detects face, human body, vehicle and non-motor automatica-ly detection and capture |
| INTERFACE | |
| Ethernet | 1 Ethernet (10/100 Base-T) RJ-45 Connector |
| Audio | 1ch Input, 1ch Output |
| Alarm | 1ch Input, 1ch Output |
| Reset Button | Support |
| Storage | Built-in Micro SD slot, up to 256Gb |
| ELECTRICAL | |
| Power Supply | DC12V/POE (IEEE 802.3af) |
| Power Consumption | <8.5W |
| Operating Temperature | -30°C ~ 50°C (-22°F ~ 122°F) |
| Operating Humidity | Less than 90% RH |
| Ingress Protection | IP66 |
| Certifications | CE / FCC |
| Casing | Metal |
| Dimensions | 232x74.8x80mm |
| Net Weight | 750g |