



SPA 4210IP

IP AUDIO TERMINAL

Siera manufactures reliable and affordable solutions in Electronic Security, CCTV, Access Control, Intercommunications, Professional Audio and Automation.

Featured specifications

- High-end brushed aluminum cover and anti-dust shield
- 3-inch LCD screen (128x64), 16 metal digit keys on the panel and an infrared remote controller to play the audio file
- Built-in digital amplifier of Class D and voice output
- Microphone on the terminal to enable the main control room
- Broadcast to other IP terminals
- Standard RJ45 interface

Power Supply And Consumption:	DC12v/2A, ≤24W
Network Protocol:	TCP/IP, UDP, ARP, ICMP, IGMP
Network Chip Rate:	10/100Mbps
Audio Sampling & Bit Rate:	8kHz~44.1kHz, 16bit, 8kbps~320kbps
S/n:	≥90db, 20Hz~16kHz
Network Delay:	Broadcast Delay ≤30ms, Intercom Delay ≤30ms
Power Output:	2x10W(8Ω)
Interface:	1 RJ-45 Port, 1 Microphone Input, 2 Line In, 1 Line Out, 1 Alarm Out, 2 Power Output, 1 USB Port, 1 Constant Voltage Backup Input (Optional)
Working Temp & Humidity:	-0°C ~ 45°C, ≤90%Rh (Not Condensing)
Dimensions & Weight:	256x186x49mm; 1.8kg

