Siera Electronics



PRO 9050IP-8MPX-IVS

8MPX XTREME PROFESSIONAL
IP Bullet Camera with IVS

Siera manufactures reliable and affordable solutions in Electronic Security, CCTV, Access Control, Intercommunication and Professional Audio.

Featured specifications

- 1/2.5'' Progressive Scan CMOS
- 2.7-13.5mm Motorized lens
- 15fps@8MP(3840 x 2160)
- Multiple Streams
- Smart IR Up to 40m
- Low bitrate control
- 3D DNR, WDR, ICR
- Support ROI, Corridormode, HLC
- Slot SD Card
- Alarm I/O
- Audio I/O
- FREE Siera DDNS
- FREE IPX-PRO V4 VMS
- FREE APP for iOS / Android
- ONVIF

WARRANTY 3 YEARS

Image Sensor:	1/2.5" Progressive Scan CMOS
Min. Illumination:	Color: 0.005Lux@ (F1.2,AGC ON); B/W: 0 Lux@ (IR LED ON)
Day & Night:	ICR
Shutter Speed:	1/2-1/100000s
Auto Iris:	Auto Iris
Wide Dynamic Range:	WDR >120dB
Digital Noise Reduction:	2D/3D
Lens:	2.7-13.5mm motorized lens (autofocus)
FOV:	100°-35°
IR LED:	30pcs
IR Range:	40mts
IMAGE	
Video Compression:	H.265 / H.264 / MJPEG
Bit Rate (CBR / VBR):	Stream1:500kbps ~ 16000kbps; Stream2:32kbps ~ 6000kbps
Audio Compression:	G.711 ,RAW_PCM
Max. Resolution:	3840*2160/15fps
Stream:	Stream1: 3840x2160@20fps, 2560x1920, 2592x1520 / 2560x1440 @25/30fps 2048x1536/1920x1080:25/30fp Stream2: 1280x720 / D1 / VGA / CIF / QVGA @25/30fps
Image Setting:	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
HLC:	Yes
9:16 Corridor Mode:	Yes
ROI:	Yes
Network Protocols:	IPv4/IPv6, APR, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE SMTP, DNS, UPnP, FTP, ICMP, IGMP, SNMP, Unicast and Multicast
Alarm Trigger:	Perimeter, Single Virtual Fences, Double Virtual Fences, Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed, Converse, Illegal Parking, Signal Bad, Motion, Detection, Network disconnect, Facial detection, Scene Change, Image Tamper, Detection of baggage/object (Human/Vehicle)
RTSP Video:	Standard RFC2326, Support QuickTime / VLC Player
Security:	User security authentication, Reset, Hardware WatchDog
WEB Language:	English, Portuguese, Spanish
System Compatibility:	Onvif (API/SDK)
Ethernet:	1 Ethernet (10/100 Base-T) RJ-45 Connector
Power Supply:	DC12V/POE
Power Consumption:	2.5W (IR LED OFF); 5W (IR LED ON)
Operating Temperature:	-25°C ~ 55°C (-13°F ~ 131°F)
Operating Humidity:	0% - 90% RH
Ingress Protection:	IP66 / IK10
Approvals:	CE / FCC
Product Dimensions:	232 × 74.8 × 80mm
Product Weight:	670g

Siera reserves the right to apply changes on the specifications of the products at any moment without prior notice.
The picture and images are as reference only, the product can vary from reality. Siera is a trademark belonging to the Siera Holding Group.